



## DT-5K-FSR

Keyboard with Integrated Force Sensing Resistor

The DT-5K-FSR from iKey combines a Force Sensing Resistor, an upgraded pointing device that offers improved sensitivity and increased durability, with a 10-key numeric keypad in a ruggedized stainless steel case, providing dual functionality in one compact unit. Its 20 function keys provide user versatility. This keyboard also offers user Windows keys for ease of access to the operating system. Features:

10-Key Numeric Pad

113-Key Functionality

20 Function Keys

Integrated Force Sensing Resistor Pointing Device USB and PS/2 Configurations Available

## Product Code DT-5K-FSR

COMPATIBILITY  PS/2 KEYBOARD/POINTER: All Windows Opera and Macintosh OS  TEMPERATURE RANGE  STORAGE: -40C to +70C (-40F to +158F) OPER  WARRANTY  1 Year Limited Warranty  HUMIDITY  100% Humidity Resistant  DIMENSIONS  16.25" x 7.88" x 1.80" (w-h-d) 412.8mm x 200.2m	
and Macintosh OS  TEMPERATURE RANGE STORAGE: -40C to +70C (-40F to +158F) OPER  WARRANTY 1 Year Limited Warranty	RATING: -20C to +60C (-4F to +140F)
and Macintosh OS  TEMPERATURE RANGE STORAGE: -40C to +70C (-40F to +158F) OPER	RATING: -20C to +60C (-4F to +140F)
and Macintosh OS	RATING: -20C to +60C (-4F to +140F)
COMPATIBILITY	
	ating Systems USB KEYBOARD/POINTER: All Windows
POWER PS2: KEYBOARD: 35mA@5V (from Keyboard p 40mA@5V (from USB port)	ort) POINTER: 5mA@5V (from Mouse port) USB:
VIBRATION POWER SPECTRAL DENSITY: 0.04g/Hz FREQ PER AXIS: 3 hours	QUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST
KEY SWITCH	ater than 10 million cycles TRAVEL: 0.055 in. (1.4 mm) +/- 20g) FEEDBACK: Tactile with mechanical snap
CABLE LENGTH: 10 feet (3 meters) DESIGN: "Y" PS/2 connections), or Single-Cable USB	Cable (providing separate keyboard and mouse
SHOCK 3 x 11 ms pulses of 50g on each of 3 axes	
CERTIFICATIONS NEMA 4X UL60950, FCC Part 15 Class B	