

## IK-KV-11.6W

### IK-KV-11.6W Flat Panel Display

New! IK-KV-11.6w is our newest rugged LCD touch-screen display, at 11.6" wide. It is a high-bright, daylight readable flat panel display with a two-point capacitive touch screen and integrated speakers. *The night mode feature allows for a quick transition from lowest brightness to highest brightness to accommodate day vs. night setting.*

Connect to this display with a S9/S10 Samsung phone with the Samsung Dex. You can also connect your Samsung Tablet directly to the 11.6" iKey Display with a single cable. Resolution: 1920(RGB) x 1080. Fully mountable, IK-KV-11.6 is ideal for vehicle mount and most public safety vehicles. VESA Mounting Pattern: 6-32 Threaded Inserts in 75mm x 75mm Pattern.

#### Features:

- Two-Point Capacitive Touch Screen
- 3 USB Type A ports, 1 USB 3.0 Type A upstream port
- Video input: HDMI or USB-C
- Power supply: 12VDC
- Color: Black
- Night mode
- Temperature Range: Operating 0°C to 50°C, Storage: -20°C to 60°C
- Mounting: VESA 75mm x 75mm pattern

Please download the "Info Sheet" in the downloads section for all specs and photos.

Check out our new video.



## Product Code IK-KV-11.6W

LCD SIZE	11.6"
RESOLUTION	1920 x 1080
DISPLAY MODE	Normally black
POWER	12 VDC
INPUT	MONITOR: HDMI, TOUCHSCREEN: USB

BUTTON FUNCTIONS	Power, Menu, Volume Up/Down, Brightness Up/Down, Night Mode, Blackout
TEMPERATURE RANGE	STORAGE: -4F to +140F (-20C to 60C) OPERATING: 32F to +122F (0C to 50C)
PIXEL ARRANGEMENT	RGB Vertical Stripe
THERMAL SHOCK	Should be able to withstand 6 cycles. (1 cycle: -20/30min change interval~ +60 C/ 30 min, 5 min change interval)
MOUNTING PATTERN	VESA 75mm x 75mm
HUMIDITY	10-90% (No Condensation)
WEIGHT	3.0 lbs
Dimensions	11.71"x 8.21"x 1.36" (l-w-d) 297.1mm x 208.5mm x 34.5mm