IK-PAN-FZG1-C1-V5

Keyboard for Panasonic FZG1 Panasonic Tablet

The IK-PAN-FZG1-C1-V5 iKey keyboard, specifically designed to attach to the Panasonic® FZG1 Tablet. The V5 is improved from previous models, designed with a more robust latching mechanism which provides increased docking strength while reducing wear and tear on the keyboard. The new latching mechanism now locks and secures the keyboard to the tablet and does not require a key of any kind. This model specifically includes Green backlighting and 1x external USB 2.0 port.

- EASILY CLEAN WITH HOSPITAL-APPROVED METHODS SUCH AS 99.9% ISOPROPYL RUBBING ALCOHOL, WIPES, OR A BLEACH SOLUTION (10% BLEACH/90% WATER, UP TO 70% BLEACH. ADVISE: PUT SOLUTION ON PAPER TOWEL, WIPE OR CLEANING MATERIAL.)

This rugged keyboard is resistant to dirt, dust and spills. It is rated IP54. Splashes of water and most liquids will have no harmful effect. It is made of industrial silicone rubber.The keyboard is a full QWERTY keyboard with integrated touchpad.
See the video: https://youtu.be/VmV6IRNBWT8
iKey keyboard is designed specifically for use with the Panasonic FZG1 Tablet. This keyboard is very easy to clean and disinfect with hospital-approved methods including rubbing alcohol and bleach solutions. These cleansers will not hurt the keypad.

## Product Code IK-PAN-FZG1-C1-V5

| MATERIAL | Industrial Silicone Rubber |
|---|---|
| TEMPERATURE RANGE | STORAGE: -40 F to +185 F (-40 C to 85 C)OPERATING: 14 F to 122 F (-10 C to +50 C), TEMPERATURE SHOCK: -40 F to 185 F (-40 C to 85 C) Within 15 seconds, 2 Hour Dwells |
| VIBRATION | STANDARD: MIL-STD810G 514.6, OPERATIONAL: 2 cycles/ Axis (1 Hour/Cycle) 10 to 500 Hz NON-OPERATIONAL: 2 cycles/ Axis (1 Hour/Cycle) 20 to 2000Hz |
| KEY SWITCH | MATERIAL: Industrial Silicone Rubber LIFE: Greater than 10 Million Cycles TRAVEL: 0.055in ACTUATION FORCE: 7.03 oz +/-1.06 oz (200g +/-30g) FEEDBACK: Tactile with Mechanical Snap |

| | |
|---|---|
| SHOCK | STANDARD: MIL-STD810G 514.6 OPERATIONAL: 1.15Grms NON-OPERATIONAL: 7.89Grms |
| POWER | USB: MAX 235mA@5V, 1X External 2.0 USB port |
| DIMENSIONS | 243.332mm x 277.876mm (9.58 inches by 10.94 inches) |
| WEIGHT | 2.1 lbs +/- 0.10 lbs (0.95 kg +/- 0.05 kg) |
| RATING | IP54 |