



PM-102-TP

Panel Mount Keyboard with Touchpad

iKey's SlimKey® PM-102-TP panel mount keyboard provides full-size versatility in a rugged, compact design with the added convenience of an integrated touchpad. Engineered for NEMA 4X protection from dust, water and corrosive liquids, the PM-102-TP is ideal for use in environments ranging from manufacturing to material handling to medical settings. Its large numeric pad allows for easy data entry, while its robust polycarbonate case protects it against any hazardous environment.

Features:

- 104-Key Functionality
- Industrial Silicone Rubber Keypad
- Integrated Touchpad
- Lightweight ABS Polycarbonate Case
- Low-profile keys for easy cleaning
- MS Windows™ Function Keys

Product Code PM-102-TP

| | |
|-------------------|--|
| CERTIFICATIONS | NEMA 4X, CE UL60950, FCC Part 15 Class B |
| SHOCK | 3x11 ms pulses of 50g on each of 3 axes |
| CABLE | 10 feet (3 meters) |
| KEY SWITCH | MATERIAL: Industrial Silicone Rubber LIFE: Greater Than 10 Million Cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION FORCE: 7.05 oz. +/- 1.06 oz. (200g +/- 30g) FEEDBACK: Tactile with Mechanical Snap |
| VIBRATION | POWER SPECTRAL DENSITY: 0.04g ² /Hz FREQUENCY RANGE: 20Hz - 2kHz DURATION OF TEST PER AXIS: 3 hours |
| POWER | PS/2: KEYBOARD: 50mA@5V (from Keyboard port) POINTER: 10mA@5V (from Mouse port) USB: 60mA@5V (from CPU port) |
| COMPATABILITY | KEYBOARD: PS/2: All Windows Operating Systems; USB: All Windows and Macintosh OS GLIDEPOINT: PS/2: All Windows Operating Systems; USB: All Windows and Macintosh OS |
| TEMPERATURE RANGE | STORAGE: -40C to +65C (-40F to +149F) OPERATING: 0C to +60C (32F to 140F) |
| WEIGHT | 1.50 lbs +/- 0.10 lbs (0.68 kg +/- 0.05 kg) |
| WARRANTY | 1 Year Limited Warranty |
| HUMIDITY | 100% Humidity Resistant |
| DIMENSIONS | 15.10" x 6.05" x 0.59" (w-h-d) 383.5mm x 153.7mm x 15mm SCREWS: 0.50" (12.7mm) |

MODEL NUMBERS

PM-102-TP-PS2: With PS/2 cable PM-102-TP-USB: With USB cable
