



RDC-5K-FSR

Rackdrawer Keyboard with Force Sensing Resistor

The RDC-5K-FSR by iKey integrates a Force Sensing Resistor pointing device and a full numeric keypad for dual functionality. Standard size units have 14-inch rails (15-inch-deep drawer) and come with chrome handle or pull slot options. Larger size units have 16-inch rails (17-inch drawer) and come with T-handle or locking T-handle options. The drawers have a CRS steel construction, which is coated with black epoxy paint and chrome-plated, ball-bearing slides.

Features:

10-Key Numeric Pad

20 Function Keys

Integrated Force Sensing Resistor Pointing Device

Slide Load Rating: 130 Lbs/Pair

USB and PS/2 configurations available

Product Code RDC-5K-FSR

| | |
|-------------------|--|
| CERTIFICATIONS | NEMA 12, CE UL60950, FCC Part 15 Class B |
| SHOCK | 3x11 ms pulses of 50g on each of 3 axes |
| CABLE | LENGTH: 10 feet (3 meters) DESIGN: "Y" PS/2 (providing separate keyboard and mouse connections), or Single-Cable USB |
| KEY SWITCH | MATERIAL: Industrial silicone rubber LIFE: 10 million cycles TRAVEL: 0.055 in. ACTUATION FORCE: 7.03 oz +/-1.06 oz (200g +/- 20g) FEEDBACK: Tactile with mechanical snap |
| VIBRATION | POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours |
| POWER | PS/2: KEYBOARD: 50mA@5V (from Keyboard port) POINTER: 35mA@5V (from Mouseport) USB: 85mA@5V (from CPU port) |
| COMPATIBILITY | PS/2 KEYBOARD/POINTER: All Windows Operating Systems USB KEYBOARD/POINTER: All Windows and Macintosh OS |
| TEMPERATURE RANGE | STORAGE: -40C to +70C (-40F to 158F) OPERATING: -4C to +60C (-20F to +60F) |
| WEIGHT | 12.80 lbs +/- 0.10 lbs (5.8 kg +/-0.05 kg) |
| WARRANTY | 1 year limited warranty |
| HUMIDITY | 100% |
| DIMENSIONS | Pull Slot/Chrome handle: 19" x 15" x 1U (1.75") 482.6mm x 381mm x 44.5mm T-Handle: 19" x 17" x 1U (1.75") 482.6mm x 431.8mm x 44.5mm |

MODEL NUMBERS

RDC-5K-PS2: With PS/2 cable RDC-5K-USB: With USB cable RDC-5K-16-T-xxx: 16" Rails T-Handle
RDC-5K-16-TK-xxx: 16" Rails T-Handle with Key
