

SK-102-TP

SlimKey™ Keyboard with Touchpad

iKey's SlimKey® SK-102-TP keyboard provides full-size versatility in a rugged, compact design with the added convenience of an integrated touchpad. Engineered for NEMA 4X protection from dust, water and corrosive liquids, the SlimKey SK-102-TP is ideal for use in environments ranging from manufacturing to material handling to medical settings. Its large numeric pad allows for easy data entry, while its robust polycarbonate case protects it against any hazardous environment.

Features:

- 10-Key Numeric Pad
- Industrial Silicone Rubber Keypad
- Integrated Touchpad
- Lightweight ABS Polycarbonate Case
- Low-profile keys for easy cleaning
- MS Windows™ Function Keys



Product Code SK-102-TP

CERTIFICATIONS	NEMA 4X, CE UL60950, FCC Part 15 Class B
SHOCK	3x11 ms pulses of 50g on each of 3 axes
CABLE	10 feet (3 meters) DESIGN: "Y" PS/2 and Serial Cable (providing separate keyboard and mouse connections), or Single-Cable USB
KEY SWITCH	MATERIAL: Industrial silicone rubber LIFE: Greater than 10 million cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION FORCE: 7.05 oz +/- 1.06 oz (200g +/- 30g) FEEDBACK: Tactile with mechanical snap
VIBRATION	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2kHz DURATION OF TEST PER AXIS: 3 hours
POWER	PS/2: KEYBOARD: 50mA@5V (from Keyboard port) TOUCHPAD: 10mA@5V (from Mouse port) USB: 60mA@5V (from CPU port)
COMPATABILITY	KEYBOARD: PS/2: All Windows Operating Systems; USB: All Windows and Macintosh OS GLIDEPOINT: PS/2: All Windows Operating Systems; USB: All Windows and Macintosh OS
TEMPERATURE RANGE	STORAGE: -40C to +65C (-40F to +149F) OPERATING: 0C to +60C (+32F to +140F)
WEIGHT	1.5 lbs +/- 0.10 lbs (0.68 kg +/- 0.05 kg)
WARRANTY	1 Year Limited Warranty
HUMIDITY	100%
DIMENSIONS	14.60"x 5.55" x 0.93" (w-h-d) 370.8mm x 141.0mm x 23.6mm

MODEL NUMBERS

SK-102-TP-PS2: With PS/2 cable SK-102-TP-USB: With USB cable
