

SL-75-OEM

OEM Compact Keyboard

The compact SL-75-OEM keyboard by iKey is excellent for integration into industrial and mobile applications. This rugged keyboard is designed to meet NEMA 4X specifications when properly installed. The SL-75-OEM kit includes an industrial silicone rubber pad, board and cable. The SL-75-OEM features red LED backlit keys for use in areas with minimal lighting and 75 keys, including 12 function keys.

Features:

Red Backlit Keys

USB, PS/2 and AT/serial configurations available



Product Code SL-75-OEM

| | |
|-------------------|---|
| CERTIFICATIONS | NEMA 4X, CE UL60950, FCC Part 15 Class B |
| SHOCK | 3 x 11 ms pulses of 50g on each of 3 axis |
| CABLE | LENGTH: 10 feet straight (3 m) |
| KEY SWITCH | MATERIAL: Industrial Silicone Rubber LIFE: Greater than 10 million cycles TRAVEL: 0.055 in. ACTUATION FORCE: 4.76 oz. (135g) FEEDBACK: Tactile with Mechanical Snap |
| VIBRATION | POWER SPECTRAL DENSITY: .04g/HZ FREQUENCY RANGE: 20Hz-2Khz DURATION OF TEST PER AXIS: 3 hours |
| POWER | PS/2: 200mA@5V (from Keyboard port) USB: 200mA@5V (from CPU port) |
| COMPATABILITY | PS/2: All Windows Operating Systems USB: All Windows and Macintosh OS |
| TEMPERATURE RANGE | STORAGE: -40F to +194F (-40C to +90C) OPERATING: -40F to +158F (-40C to +70C) |
| WEIGHT | 0.75 lbs +/- 0.10 lbs (0.34 kg +/- 0.05kg) |
| WARRANTY | 90 Day Limited Warranty |
| HUMIDITY | 100% Humidity Resistant (when properly installed) |
| DIMENSIONS | 7.85" x 3.85" x 0.36" (w-h-d) 199.4 x 97.8 x 9.1 mm |
| MODEL NUMBERS | SL-75-OEM-PS2: With PS/2 Cable SL-75-OEM-USB: With USB Cable SL-75-OEM-STD: With AT/Serial Cable |