



SL-75

Compact Mobile Keyboard

The compact SL-75 by iKey is excellent in mobile applications where there is limited space available. This rugged keyboard is designed to meet NEMA 4X specifications. It is built with an industrial silicone rubber keypad and a black aluminum case. The SL-75 features red LED backlit keys for use in areas with minimal lighting and 75 keys, including 12 function keys.

Features:

Red Backlit Keys

USB, PS/2 and AT/serial configurations available

Product Code SL-75

CERTIFICATIONS	NEMA 4X, CE UL60950, FCC Part 15 Class B
SHOCK	3 x 11 ms pulses of 50g on each of 3 axes
CABLE	LENGTH: 10 feet straight (3 m)
KEY SWITCH	MATERIAL: Industrial Silicone Rubber LIFE: Greater than 10 million cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION FORCE: 4.76 oz. +/- 1.06 oz (135g +/- 30g) FEEDBACK: Tactile with Mechanical Snap
VIBRATION	POWER SPECTRAL DENSITY: .04g/HZ FREQUENCY RANGE: 20Hz-2Khz DURATION OF TEST PER AXIS: 3 hours
POWER	PS/2: 200mA@5V (from Keyboard port) USB: 200mA@5V (from CPU port)
COMPATABILITY	PS/2: All Windows Operating Systems USB: All Windows and Macintosh OS
TEMPERATURE RANGE	STORAGE: -40C to +90C (-40F to +194F) OPERATING: -40C to +70C (-40F to +158F)
WEIGHT	1.25 lbs +/- 0.10 lbs (0.57 kg +/- 0.05 kg)
WARRANTY	1 Year Limited Warranty
HUMIDITY	100% Humidity Resistant
DIMENSIONS	8.25" x 4.34" x 1.08" (w-h-d) 209.6 x 110.2 x 27.4
MODEL NUMBERS	SL-75-PS2: With PS/2 Cable SL-75-USB: With USB Cable SL-75-STD: With AT/Serial Cable