SL-86-911-TP-FL

Keyboard with Touchpad

The SL-86-911-TP-FL keyboard by iKey(R) is designed for in-vehicle use for emergency, police, service, transport trucks and marine vessels. Built for convenience and versatility in mobile computing applications, at just 1.27? thick, this model lies extremely flat and doesn't take up extra space. Features include a user-friendly integrated touchpad, backlit keys for low-light environments, a one-touch emergency key. The new, easy-to-use integrated touchpad was created to meet public demand for a user-friendly alternative to the traditional HulaPoint(R) pointing device.

Features:

86-Key Functionality

Fn Key for Secondary Legend Flexibility

Integrated Touchpad

Meets NEMA 4X (IP65) Specifications

One-Touch Emergency Key

Red Backlit Keys

Note*** This model does not feature mounting holes.

If you require mounting holes please look at the SL-86-911-TP

## Product Code SL-86-911-TP-FL

| | |
|---|---|
| CERTIFICATIONS | NEMA 4X UL60950, FCC Part 15 Class B |
| SHOCK | 3x11 ms pulses of 50g on each of 3 axes |
| CABLE | LENGTH: 4 ft coiled (1.2m) DESIGN: "Y" PS/2 (providing separate keyboard and mouse connections), or Single-Cable USB |
| KEY SWITCH | MATERIAL: Industrial Silicone rubber LIFE: Greater than 10 million cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION FORCE: 7.05 oz. +/- 1.06 oz. (200g +/- 30g) FEEDBACK: Tactile with mechanical snap |
| VIBRATION | POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2kHz DURATION OF TEST PER AXIS: 3 hours |
| POWER | KEYBOARD: 200mA@5V (from Keyboard port) TOUCHPAD: 10mA@5V (from mouse port) USB: 210mA@5V (from CPU port) |
| FLAMMABILITY | PRINTED CIRCUIT BOARD: 94 VO SILICONE OVERLAY: 94 HB INTERFACE CABLE: 94 VO |
| COMPATABILITY | PS/2 KEYBOARD/HULAPOINT: All Windows Operating Systems USB KEYBOARD/HULAPOINT: All Windows and Macintosh OS |

| | |
|---|---|
| TEMPERATURE RANGE | Storage -40C to +90C (-40F to +194F) Operating -40C to +70C (-40F to +158F) |
| WEIGHT | 2 lbs +/- 0.10 lbs (1.38 kg +/- 0.05 kg) |
| WARRANTY | 1 Year Limited Warranty |
| HUMIDITY | 100% |
| DIMENSIONS | 12.0" x 7.74" x 1.27" (w-h-d) 304.8mm x 196.6mm x 32.3mm |
| MODEL NUMBERS | SL-86-911-TP-FL-PS2: With PS/2 cable SL-86-911-TP-FL-USB: With USB cable |