

## SL-910

### Small Footprint Keyboard

iKey's SL-910 mobile keyboard was designed with material handling applications in mind. Set apart by its uniquely spaced layout and arranged for convenient gloved-hand use. It features a small-footprint design, mounting holes in its case, and a 10-key numeric pad for easy numeric data entry. Like other keyboards in the iKey line, the SL-910 is constructed using a robust polycarbonate case and industrial silicone keypad, sealing it from dust, liquids, and corrosives.

#### Features:

24 Function Keys

Built-In Mounting Holes (AMPS)

Integrated 10-Key Numeric Pad

Integrated Backlighting

Lightweight ABS Polycarbonate Case

USB, PS2, and DB9 configurations available



## Product Code SL-910

CERTIFICATIONS	NEMA 4X UL60950, FCC Part 15 Class B
SHOCK	3x11 ms pulses of 50g on each of 3 axes
CABLE	LENGTH: 4 ft coiled (1.2m) DESIGN: PS/2 or USB Cable
KEY SWITCH	MATERIAL: Industrial Silicone Rubber LIFE: Greater Than 10 Million Cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION FORCE: 7.03 oz +/- 0.70 oz (200g +/- 20g) FEEDBACK: Tactile with mechanical snap
VIBRATION	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
POWER	PS2: KEYBOARD: 200mA@5V (Keyboard port) USB: 200mA@5V (from CPU port)
COMPATABILITY	PS/2 KEYBOARD: All Windows Operating Systems USB KEYBOARD: All Windows and Macintosh OS
TEMPERATURE RANGE	STORAGE: -40C to +90C (-40F to +194F) OPERATING: -40C to +70C (-40F to +158F)
WEIGHT	2.25 lbs +/- 0.10 lbs (1.02 kg +/- 0.05 kg)
WARRANTY	1 Year Limited Warranty
HUMIDITY	100% Humidity Resistant
DIMENSIONS	11.40" x 6.30" x 1.90" (w-h-d) 289.6mm x 160.0mm x 48.3mm

MODEL NUMBERS

SL-910-PS2: With PS/2 cable SL-910-USB: With USB cable SL-910-DB9-3F: With 3 foot DB9 cable  
(configured USB)

---