



### SLK-79-OEM-FSR

#### Backlit OEM Keyboard with Force Sensing Resistor

The SLK-79-OEM-FSR is a small-footprint keyboard that easily integrates into various applications. Featuring a Force Sensing Resistor pointing device with dual left-click capability, the SLK-79-OEM-FSR offers a large amount of functionality in an ultra-small package. It is manufactured with red LED backlit keys for use in low-light environments. It is designed to meet NEMA 4X specifications when properly installed.

#### Features:

- 12 Function Keys
- Dual Left Click Function
- Integrated Backlighting
- Integrated Force Sensing Resistor Pointing Device
- Optional NVIS Compliant – Green B backlighting

## Product Code SLK-79-OEM-FSR

Certifications	NEMA 4X, CE UL60950, FCC Part 15 Class B
Shock	3 x 11 ms pulses of 50g on each of 3 axis
Cable	3' (0.91 m)
Key Switch	MATERIAL: Industrial Silicone Rubber LIFE: Greater than 10 Million Cycles TRAVEL: 0.055 in. ACTUATION FORCE: 135g FEEDBACK: Tactile with Mechanical Snap
Vibration	POWER SPECTRAL DENSITY: .04g/HZ FREQUENCY RANGE: 20Hz-2Khz DURATION OF TEST PER AXIS: 3 hours
Power	PS/2: KEYBOARD: 200mA@5V (from Keyboard port) POINTER: 35mA@5V (from Mouse port) USB: 235mA@5V (from CPU port)
Comptability	PS/2: All Windows Operating Systems USB: All Windows and Macintosh OS
Temperature Range	STORAGE: -40C to +70C OPERATING: -20C to +60C
Weight	0.75 lbs (0.34 kg)
Warranty	1 year limited warranty
Humidity	100% Humidity Resistant
Dimensions	9.00" x 3.60" x 0.45" (w-h-d) 228.6mm x 91.4mm x 11.4mm
Model Number	SLK-79-OEM-FSR-PS2: With PS/2 cable SLK-79-OEM-FSR-USB: With USB cable