



SLP-91

Panel Mount Keyboard with Epoxy Keycaps

iKey's innovative SLP-91 panel mount keyboard was designed to accommodate rugged applications in manufacturing, material handling and data entry. Its unique epoxy-coated keys are arranged for convenient gloved-hand use. It features a small-footprint design, backlit keys and a 10-key numeric pad. Like other keyboards in the iKey line, the SLP-91 is constructed with an industrial silicone keypad, sealing it from dust, liquids and corrosives.

Features:

- 24 Function Keys
- Integrated 10-Key Numeric Pad
- Integrated Backlighting
- USB and PS/2 configurations available

Product Code SLP-91

CERTIFICATIONS	NEMA 4X UL60950, FCC Part 15 Class B
SHOCK	3x11 ms pulses of 50g on each of 3 axes
CABLE	LENGTH: 4 ft coiled (1.2m) DESIGN: PS/2 or USB Cable
KEY SWITCH	MATERIAL: Epoxy-Coated Industrial Silicone Rubber LIFE: Greater than 10 Million Cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION FORCE: 7.03 oz. +/- 0.70 oz. (200g +/- 20g) FEEDBACK: Tactile with Mechanical Snap
VIBRATION	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
POWER	PS/2: KEYBOARD: 200mA@5V (from Keyboard port) USB: 200mA@5V (from CPU port)
COMPATABILITY	PS/2 KEYBOARD: All Windows Operating Systems USB KEYBOARD: All Windows and Macintosh OS
TEMPERATURE RANGE	STORAGE: -40C to +90C (-40F to +194F) OPERATING: -40C to +70C (-40F to +158F)
WEIGHT	1.75 lbs (0.80 kg)
WARRANTY	1 year limited warranty
HUMIDITY	100%
DIMENSIONS	11.80" x 6.79" x 0.70" (w-h-d) 299.7mm x 172.5mm x 17.8mm SCREWS: 0.75" (19.1mm) CUTOUT: 10.40" x 5.40" (w-h) 264.2mm x 137.2mm
MODEL NUMBERS	SLP-91-PS2: With PS/2 cable SLP-91-USB: With USB cable